



### Indoor WDR Hi-Res Dome Camera

1/3" Sony Super HAD CCD II, 600 TV Line Resolution, 0.0001Lux, Day & Night Function, OSD, 3 Axis, 3.6mm Lens, DC12V






#### Specifications

Model	SVD632
Resolution	600 TV Lines
Sensor	1/3 inch SONY DS CCD
Total Pixels	811(H) x 508(V) 410K pixels (NTSC) 795(H) x 595(V) 470K pixels (PAL)
Effective Pixels	768(H) x 494(V) 380K pixels (NTSC) 752(H) x 582(V) 440K pixels (PAL)
Scanning System	2:1 Interlace
Synchronization	Internal / Line Lock
Frequency	Horizontal : 15.734KHz / Vertical : 59.94Hz (NTSC) Horizontal : 15.625KHz / Vertical : 50.00Hz (PAL)
S/N (Y signal)	More than 50 dB (AGC off)
Video Output	CVBS : 1.0Vp-p / 75ohm
Min. Illumination	0.1 Lux at F1.2 (Color) / 0.0001 Lux (Sense-up x256)
White Balance	ATW / AWC / PUSH / MANUAL
Electronic shutter Speed	Auto / Manual (1/60 sec ~ 1/120,000 sec NTSC) (1/50 sec ~ 1/120,000 sec PAL) Sense-up and sense-up limit is selectable / Flickerless
Sens-Up	AUTO / OFF (selectable limit x2 ~ x256)
O.S.D	Built-in
Backlight Compensation	Low, Middle, High, HLM, Off Selectable
Gain Control	Low, Middle, High, Off Selectable
3DDNR (3D Digital Noise Reduction)	Low, Middle, High, Off Selectable
Day & Night	Auto, Color, B/W, CDS
SYNC	INTERNAL / AUTO
Motion Detection	ON / OFF
PRIVACY	ON / OFF (6 Zone)
WDR (Long and Short exposure)	ON / OFF
Digital Zoom	ON (x10) / OFF
MIRROR (H-REV)	MIRROR / V-FLIP / ROTATE / Off
Operating Temperature / Humidity	-10 deg.C ~ +50 deg.C / 30%~ 80% RH
Storage Temperature / Humidity	-20 deg.C ~ +60 deg.C / 20% ~ 90% RH
POWER	DC12V Only
Lens (Selective)	Fixed Lens 3.6mm

#### Features

- WDR (Wide Dynamic Range)
- 600 TV Line Resolution
- 1/3" SONY Super HAD CCD II
- Digital Zoom (x1~x10)
- 3DDNR (3D Digital Noise Reduction)
- LSC (Lens Shading Compensation)
- DIS (Digital Image Stabilizer)
- 0.1Lux at F1.2 (Color) / 0.0001Lux (Sense-up x256)
- Day and Night Function
- Electronic Shutter Control(ESC)
- Controlled by OSD Menu
- Privacy Function
- Motion Detection
- Easy Installation & 3-Axis



Made in Korea

3 Year Warranty



### Indoor WDR Hi-Res Dome Camera

1/3" Sony Super HAD CCD II, 600 TV Line Resolution, 0.0001Lux, Day & Night Function, OSD, 3 Axis, 3.6mm Lens, DC12V






#### Specifications

<b>Model</b>	SVD632
Resolution	600 TV Lines
Sensor	1/3 inch SONY DS CCD
Total Pixels	811(H) x 508(V) 410K pixels (NTSC) 795(H) x 595(V) 470K pixels (PAL)
Effective Pixels	768(H) x 494(V) 380K pixels (NTSC) 752(H) x 582(V) 440K pixels (PAL)
Scanning System	2:1 Interlace
Synchronization	Internal / Line Lock
Frequency	Horizontal : 15.734KHz / Vertical : 59.94Hz (NTSC) Horizontal : 15.625KHz / Vertical : 50.00Hz (PAL)
S/N (Y signal)	More than 50 dB (AGC off)
Video Output	CVBS : 1.0Vp-p / 75ohm
Min. Illumination	0.1 Lux at F1.2 (Color) / 0.0001 Lux (Sense-up x256)
White Balance	ATW / AWC / PUSH / MANUAL
Electronic shutter Speed	Auto / Manual (1/60 sec ~ 1/120,000 sec NTSC) (1/50 sec ~ 1/120,000 sec PAL) Sense-up and sense-up limit is selectable / Flickerless
Sens-Up	AUTO / OFF (selectable limit x2 ~ x256)
O.S.D	Built-in
Backlight Compensation	Low, Middle, High, HLM, Off Selectable
Gain Control	Low, Middle, High, Off Selectable
3DDNR (3D Digital Noise Reduction)	Low, Middle, High, Off Selectable
Day & Night	Auto, Color, B/W, CDS
SYNC	INTERNAL / AUTO
Motion Detection	ON / OFF
PRIVACY	ON / OFF (6 Zone)
WDR (Long and Short exposure)	ON / OFF
Digital Zoom	ON (x10) / OFF
MIRROR (H-REV)	MIRROR / V-FLIP / ROTATE / Off
Operating Temperature / Humidity	-10 deg.C ~ +50 deg.C / 30%~ 80% RH
Storage Temperature / Humidity	-20 deg.C ~ +60 deg.C / 20% ~ 90% RH
POWER	DC12V Only
Lens (Selective)	Fixed Lens 3.6mm

#### Features

- WDR (Wide Dynamic Range)
- 600 TV Line Resolution
- 1/3" SONY Super HAD CCD II
- Digital Zoom (x1~x10)
- 3DDNR (3D Digital Noise Reduction)
- LSC (Lens Shading Compensation)
- DIS (Digital Image Stabilizer)
- 0.1Lux at F1.2 (Color) / 0.0001Lux (Sense-up x256)
- Day and Night Function
- Electronic Shutter Control(ESC)
- Controlled by OSD Menu
- Privacy Function
- Motion Detection
- Easy Installation & 3-Axis



Made in Korea

3 Year Warranty