

Suzuki Burgman Oil and Filter Change

Time and Ease: Easy - under 30 minutes

Tools/Supplies: Oil, oil filter, oil wrench, drain pan, rag, funnel, socket set

Step 1: Put bike on center stand. Engine oil should be warm when changing.

Step 2: Remove maintenance lid in center hump.

Step 3: Place an oil pan below the engine and drain the oil by removing the drain plug (1) and filler cap (2).

Step 4: Remove the oil filter (1 on bottom picture) with oil filter wrench.

Step 5: Apply engine oil lightly to the gasket of the new filter before installation.

Step 6: Install the new filter turning it by hand until you feel that the filter gasket contacts the mounting surface. Then tighten it two turns using the oil filter wrench.

Step 7: Tighten the drain plug back on with a torque wrench (16.5 ft-lb).

Step 8: Refill the oil through the filler cap (2) using the scale below:

Oil change: 2.6L (2.7/2.3 US/Imp qt)

Filter change: 2.9L (3.1/2.6 US/Imp qt)

Overhaul engine: 3.4L (3.6/3.0 US/Imp qt)

Step 9: Start the engine and let it idle for 3 minutes at idling speed. Turn the engine off and let the engine settle for 3 minutes and check the oil level through the inspection glass (A). If the level is below mark "L", add oil to "F" level. If the level is above "F", drain oil to "F" level. Don't forget to recycle the oil.

