



Indoor Dome Camera

1/3" Sony Super HAD II CCD used, Day and Night Function, 0.3Lux at F1.2 (Color) / 0.03Lux (BW)






Specifications

Model	SVD562
Resolution	530 TV Lines
Sensor	1/3" SONY Super HAD II CCD
Total Pixels	811(H) x 508(V) 410K pixels (NTSC) 795(H) x 595(V) 470K pixels (PAL)
Effective Pixels	768(H) x 494(V) 380K pixels (NTSC) 752(H) x 582(V) 440K pixels (PAL)
Scanning System	2:1 Interlace
3DDNR (3D Digital Noise Reduction)	0~100 Adjustable
Frequency	Horizontal : 15.734KHz / Vertical : 59.94Hz (NTSC) Horizontal : 15.625KHz / Vertical : 50.00Hz (PAL)
S/N (Y signal)	More than 50 dB (AGC off)
Video Output	CVBS : 1.0Vp-p / 75ohm
Min. Illumination	0.3 Lux at F1.2 (Color) / 0.03Lux (BW)
White Balance	ATW / AWC / AWB <-> SET / MANUAL / INDOOR / OUTDOOR
Electronic Shutter Speed	Auto / Manual (x256 ~ 1/60 sec ~ 1/120,000 sec NTSC) (x256 ~ 1/50 sec ~ 1/120,000 sec PAL)
O.S.D	Built-in
Backlight Compensation	Low, Middle, High, HSBLCL, Off Selectable
Gain Control	Low, Middle, High, Off Selectable
Day & Night	AUTO / EXT / BW / COLOR
SYNC	Internal
Motion Detection	On / Off (4 Zone)
Privacy	On / Off (8 Zone)
Mirror	Mirror / V-FLIP / Rotate / OFF
Operating Temperature / Humidity	-10 deg.C ~ +50 deg.C / 30% ~ 80% RH
Storage Temperature / Humidity	-20 deg.C ~ +60 deg.C / 20% ~ 90% RH
Power	DC 12V
Lens (selective)	3.6mm Fixed Lens

Features

- 1/3" Sony Super HAD II CCD
- Day and Night Function
- 530 TV Line Resolution
- 0.3Lux at F1.2 (Color) / 0.03Lux (BW)
- Controlled by OSD Menu
- Electronic Shutter Control
- Privacy Function
- Motion Detection
- Easy Installation & 3 Axis



Made in Korea

3 Year Warranty



Indoor Dome Camera

1/3" Sony Super HAD II CCD used, Day and Night Function, 0.3Lux at F1.2 (Color) / 0.03Lux (BW)






Specifications

Model	SVD562
Resolution	530 TV Lines
Sensor	1/3" SONY Super HAD II CCD
Total Pixels	811(H) x 508(V) 410K pixels (NTSC) 795(H) x 595(V) 470K pixels (PAL)
Effective Pixels	768(H) x 494(V) 380K pixels (NTSC) 752(H) x 582(V) 440K pixels (PAL)
Scanning System	2:1 Interlace
3DDNR (3D Digital Noise Reduction)	0~100 Adjustable
Frequency	Horizontal : 15.734KHz / Vertical : 59.94Hz (NTSC) Horizontal : 15.625KHz / Vertical : 50.00Hz (PAL)
S/N (Y signal)	More than 50 dB (AGC off)
Video Output	CVBS : 1.0Vp-p / 75ohm
Min. Illumination	0.3 Lux at F1.2 (Color) / 0.03Lux (BW)
White Balance	ATW / AWC / AWB <-> SET / MANUAL / INDOOR / OUTDOOR
Electronic Shutter Speed	Auto / Manual (x256 ~ 1/60 sec ~ 1/120,000 sec NTSC) (x256 ~ 1/50 sec ~ 1/120,000 sec PAL)
O.S.D	Built-in
Backlight Compensation	Low, Middle, High, HSBLC, Off Selectable
Gain Control	Low, Middle, High, Off Selectable
Day & Night	AUTO / EXT / BW / COLOR
SYNC	Internal
Motion Detection	On / Off (4 Zone)
Privacy	On / Off (8 Zone)
Mirror	Mirror / V-FLIP / Rotate / OFF
Operating Temperature / Humidity	-10 deg.C ~ +50 deg.C / 30% ~ 80% RH
Storage Temperature / Humidity	-20 deg.C ~ +60 deg.C / 20% ~ 90% RH
Power	DC 12V
Lens (selective)	3.6mm Fixed Lens

Features

- 1/3" Sony Super HAD II CCD
- Day and Night Function
- 530 TV Line Resolution
- 0.3Lux at F1.2 (Color) / 0.03Lux (BW)
- Controlled by OSD Menu
- Electronic Shutter Control
- Privacy Function
- Motion Detection
- Easy Installation & 3 Axis



Made in Korea

3 Year Warranty